

MACHÓN REDUCIDO

CARACTERÍSTICAS:

- Roscado según la norma UNE-EN ISO 228-1
- **Resistencia a la tracción:** 350 N/m/n² min.
- **Alargamiento A 5:** 15% min.
- **Dureza HB:** 80% aprox.



MATERIALES:

- Latón CW617N según la norma UNE-EN 12165

DIMENSIONES:

REF	ROSCA	L (total)
2013	1/8" x 1/4"	-
2014	1/8" x 3/8"	-
2015	1/4" x 3/8"	21
2016	1/4" x 1/2"	23
2017	3/8" x 1/2"	24,5
2018	1/2" x 3/4"	29
2019	1/2" x 1"	30
2020	3/4" x 1"	31
2021	3/4" x 1 1/4"	34,5
2022	3/4" x 1 1/2"	35
2023	1" x 1 1/4"	35
2024	1" x 1 1/2"	35
2025	1" x 2"	40
2026	1 1/4" x 1 1/2"	38
2027	1 1/4" x 2"	42
2028	1 1/2" x 2"	42,5
2029	2" x 2 1/2"	54
2030	2" x 3"	57
2031	2 1/2" x 3"	62
2032	3" x 4"	-
2033	2 1/2" x 4"	-