

ARO REDUCIDO

CARACTERÍSTICAS:

- Roscado según la norma UNE-EN ISO 228-1
- **Resistencia a la tracción:** 350 N/m/n² min.
- **Alargamiento A 5:** 15% min.
- **Dureza HB:** 80% aprox.



MATERIALES:

- Latón CW617N según la norma UNE-EN 12165

DIMENSIONES:

REF	ROSCA MACHO	ROSCA HEMBRA	L (total)
2037	1/4"	1/8"	10
2038	3/8"	1/8"	13
2039	3/8"	1/4"	13
2040	1/2"	1/8"	14,5
2041	1/2"	1/4"	14,5
2042	1/2"	3/8"	14,5
2043	3/4"	1/2"	16
2044	1"	1/2"	17,5
2045	1"	3/4"	17,5
2046	1 1/4"	1/2"	19,5
2047	1 1/4"	3/4"	19,5
2048	1 1/4"	1"	19,5
2049	1 1/2"	1/2"	20,5
2050	1 1/2"	3/4"	20,5
2051	1 1/2"	1"	20,5
2052	1 1/2"	1 1/4"	20,5
2053	2"	1/2"	25,5
2054	2"	3/4"	25,5
2055	2"	1"	25,5
2056	2"	1 1/4"	25,5
2057	2"	1 1/2"	25,5
2058	2 1/2"	2"	28
2059	3"	2"	33
2060	3"	2 1/2"	33
2061	4"	2"	44
2062	4"	2 1/2"	44
2063	4"	3"	44