

UNIVERSAL COUPLING

FEATURES:

- For joining pipes with different outside diameters and/or made of different materials (such as steel, asbestos cement, ductile iron, and/or PVC)
- **Nominal pressure:** PN10/16
- **Installation:** Permits an angular deflection of 3 degrees to each side
- Designed according to UNE-EN 14525
- **With ACS producto certificate**



MATERIALS:

- **Body:** Carbon Steel Q235
- **Counter flanges:** Ductile iron EN-GJS-500-7 according to UNE-EN 1563
- **Gasket:** EPDM according to UNE-EN 681-1
- **Bolts:** Carbon steel 8.8 with Dacromet coating
- **Nuts:** Carbon steel 8.8 with Dacromet coating
- **Coating:** Blue (RAL 5015) epoxy polyamide (average thickness 250 µm) according to UNE-EN 14901-1+A1

DIMENSIONS:

REF	DN	RANGE	H	L	ØA	BOLTS	TORQUE (Nm)
4001	50	57 - 74	95	175	164	4 x M12	65 - 81
4002	65	63 - 85	95	175	182	4 x M12	65 - 81
4003	80	85 - 107	95	175	192	4 x M12	65 - 81
4005	100	107 - 132	95	175	224	4 x M12	65 - 81
4007	125	132 - 158	95	175	246	4 x M12	65 - 81
4008	150	158 - 184	115	195	283	4 x M12	65 - 81
4010	175	189 - 212	130	215	304	4 x M12	65 - 81
4012	200	218 - 244	130	215	333	4 x M12	65 - 81
4014	225	243 - 269	130	215	375	6 x M12	65 - 81
4015	250	266 - 295	170	275	394	6 x M12	65 - 81
4018	300	315 - 349	170	275	440	6 x M12	65 - 81

