

UNIVERSAL REDUCTION

FEATURES:

- For joining pipes with different outside diameters and/or made of different materials (such as steel, asbestos cement, ductile iron, and/or PVC)
- **Nominal pressure:** PN10/16
- **Installation:** Permits an angular deflection of 3 degrees to each side
- Designed according to UNE-EN 14525
- **With ACS producto certificate**



MATERIALS:

- **Body:** Carbon Steel Q235
- **Counter flanges:** Ductile iron EN-GJS-500-7 according to UNE-EN 1563
- **Gasket:** EPDM according to UNE-EN 681-1
- **Bolts:** Carbon steel 8.8 with Dacromet coating
- **Nuts:** Carbon steel 8.8 with Dacromet coating
- **Coating:** Blue (RAL 5015) epoxy polyamide (average thickness 250 µm) according to UNE-EN 14901-1+A1

DIMENSIONS:

REF	DN	RANGE		H	L	ØA	ØB	BOLTS	TORQUE (Nm)
4075	50-65	57 - 74	63 - 85	150	230	164	182	4 x M12	65 - 81
4076	50-80	57 - 74	85 - 107	150	230	164	192	4 x M12	65 - 81
4077	65-80	63 - 85	85 - 107	150	230	182	192	4 x M12	65 - 81
4078	80-100	85 - 107	107 - 132	150	230	192	224	4 x M12	65 - 81
4079	80-150	85 - 107	158 - 184	150	230	192	283	4 x M12	65 - 81
4080	100-125	107 - 132	132 - 158	150	230	224	246	4 x M12	65 - 81
4081	100-150	107 - 132	158 - 184	150	230	224	283	4 x M12	65 - 81
4082	125-150	132 - 158	158 - 184	150	230	246	283	4 x M12	65 - 81
4083	150-200	158 - 184	218 - 244	180	270	283	333	4 x M12	65 - 81
4084	175-200	189 - 212	218 - 244	180	270	304	333	4 x M12	65 - 81
4085	225-250	243 - 269	266 - 295	180	270	375	394	6 x M12	65 - 81
4086	250-300	266 - 295	315 - 349	180	270	394	440	6 x M12	65 - 81
4087	150-175	158 - 184	189 - 212	150	230	283	308	4 x M12	65 - 81

