

UNIVERSAL FLANGE ADAPTOR

FEATURES:

- For joining pipes with different outside diameters and/or made of different materials (such as steel, asbestos cement, ductile iron, and/or PVC)
- **Nominal pressure:** PN10/16
- **Installation:** Permits an angular deflection of 3 degrees
- Designed according to UNE-EN 14525
- **With ACS producto certificate**



MATERIALS:

- **Body:** Ductile iron EN-GJS-500-7 according to UNE-EN 1563
- **Counter flanges:** Ductile iron EN-GJS-500-7 according to UNE-EN 1563
- **Gasket:** EPDM according to UNE-EN 681-1
- **Bolts:** Carbon steel 8.8 with Dacromet coating
- **Nuts:** Carbon steel 8.8 with Dacromet coating
- **Coating:** Blue (RAL 5015) epoxy polyamide (average thickness 250 µm) according to UNE-EN 14901-1+A1

DIMENSIONS:

REF	DN	RANGE	H	L	ØA	BOLTS	TORQUE (Nm)
4101	50	57 - 74	75	120	164	4 x M12	65 - 81
4102	60/65/80	63 - 85	75	120	182	4 x M12	65 - 81
4103	65/80	85 - 107	75	120	192	4 x M12	65 - 81
4105	100	107 - 132	75	120	224	4 x M12	65 - 81
4107	125/150	132 - 158	75	120	246	4 x M12	65 - 81
4108	150	158 - 184	75	120	283	4 x M12	65 - 81
4110	200	189 - 212	75	120	304	4 x M12	65 - 81
4112	200	218 - 244	75	140	333	4 x M12	65 - 81
4114	250	243 - 269	85	140	375	6 x M12	65 - 81
4115	250	266 - 295	85	140	394	6 x M12	65 - 81
4118	300	315 - 349	85	140	440	6 x M12	65 - 81

