

SELF-LOCKING

FEATURES:

- To repair **PVC pipes** according to EN ISO 1452-2 and **PE pipes** according to UNE-EN 12201
Support liners are needed if PE pipes wall thickness is less than SDR17 and for molecularly oriented PVC pipes
- Nominal pressure: PN16
- Also suitable to join PVC pipes with PE pipes (place both ends of the pipes in contact)
- It is not necessary to chamfer the pipe to use it
- They have an acceptable angular deviation of 2°
- **With ACS product certificate**



MATERIALS:

- **Body:** Ductile iron EN-GJS 500-7 according to UNE-EN 1563
- **Grip rings:** Brass CW617N according to UNE-EN 12165
- **Gaskets:** EPDM according to UNE-EN 681-1
- **Bolts:** A2-70 stainless steel according to UNE-EN 3506-1. Nuts have a tefloned coating
- **Coating:** Epoxy polyamide (average thickness 250 µm, RAL 5015) according to UNE-EN 14901-1+A1

DIMENSIONS:

REF	DN	PE / PVC	A	L	BOLTS
4701	50	63	145	175	4 x M12
4702	65	75	160	180	4 x M12
4703	80	90	170	180	4 x M12
4704	100	110	190	195	4 x M12
4705	125	125	210	195	4 x M12
4712	125	140	230	215	4 x M16
4706	150	160	255	250	6 x M16
4707	200	200	295	310	6 x M16
4708	200	225	320	345	6 x M16

