

DISMANTLING JOINT

FEATURES:

- **Nominal pressure:** PN10 and PN16
- **Flange dimensions according to:** UNE-EN 1092-2



MATERIALS:

- **Body:** Ductile iron EN-GJS-500-7
- **Gasket:** EPDM according to UNE-EN 681-1
- **Bolts and nuts:** Zinc plated carbon steel (quality 8.8)
- **Coating:** Blue epoxy polyamide coating (RAL 5015), thickness 250µm



DIMENSIONS:

PN 10

REF	DN	A	B	C	L1 + TOLERANCE	L2	BOLTS
7560	50	64	125	155	195 ± 25	310	4 x M16
7561	65	78	145	185	195 ± 25	310	4 x M16
7562	80	98	160	200	205 ± 25	330	8 x M16
7563	100	118	180	220	205 ± 25	330	8 x M16
7564	125	144	210	250	205 ± 25	330	8 x M16
7565	150	170	240	265	205 ± 25	340	8 x M20
7566	200	222	295	340	210 ± 25	350	8 x M20
7567	250	274	350	400	215 ± 25	370	12 x M20
7568	300	326	400	455	230 ± 25	390	12 x M20
7569	350	378	460	505	230 ± 25	390	16 x M20
7570	400	429	515	565	245 ± 25	420	16 x M24
7571	450	480	575	625	265 ± 25	440	20 x M24
7572	500	532	620	670	270 ± 25	440	20 x M24
7573	600	635	725	780	290 ± 25	460	20 x M27
7574	700	738	840	895	290 ± 25	480	24 x M27
7575	800	842	950	1015	315 ± 25	510	24 x M30
7576	900	945	1050	1115	315 ± 25	520	28 x M30
7577	1000	1048	1160	1230	325 ± 25	550	28 x M33
7578	1200	1255	1380	1455	345 ± 25	620	32 x M36

PN 16

REF	DN	A	B	C	L1 + TOLERANCE	L2	BOLTS
7580	50	64	125	155	195 ± 25	310	4 x M16
7581	65	78	145	185	195 ± 25	310	4 x M16
7582	80	98	160	200	205 ± 25	330	8 x M16
7583	100	118	180	220	205 ± 25	330	8 x M16
7584	125	144	210	250	205 ± 25	330	8 x M16
7585	150	170	240	265	205 ± 25	340	8 x M20
7586	200	222	295	340	210 ± 25	350	12 x M20
7587	250	274	355	400	215 ± 25	380	12 x M24
7588	300	326	410	455	230 ± 25	400	12 x M24
7590	350	378	470	520	230 ± 25	400	16 x M24
7591	400	429	525	580	245 ± 25	430	16 x M27
7592	450	480	585	640	265 ± 25	450	20 x M27
7593	500	532	650	715	270 ± 25	460	20 x M30
7594	600	635	770	840	290 ± 25	500	20 x M33
7595	700	738	840	910	290 ± 25	510	24 x M33
7596	800	842	950	1025	315 ± 25	560	24 x M36
7597	900	945	1050	1125	315 ± 25	580	28 x M36
7598	1000	1048	1170	1255	325 ± 25	610	28 x M39

